

ATL-UTM

Universal Testing Machine



EPCC / PRODUCTS / APPLICATION / SOFTWARE / ACCESSORIES / CONSUMABLES / SERVICES

Analytical Technologies Limited

An ISO 9001 Certified Company

www.analyticalgroup.net

►► INCORPORATES DESIGN FEATURES TO ENABLE HIGH ACCURACY

- Loading accuracy as high as $\pm 1\%$
- Straining at variable speeds to suit a wide range of materials.
- Continuous roll autographic recorder supplied as standard to enable study of the behaviour of materials.
- Motor driven threaded columns for quick effortless adjustment of lower Crosshead to facilitate rapid fixing of test specimen.
- High reading accuracy due to large size and design of dial.
- Wide range of standard and special accessories, including load stabilizer.
- Easy change from plain to threaded and screwed specimens.
- Large effective clearance between columns enables testing of standard specimens as well as structures.
- Simple controls for ease of operation.
- Robust straining frame of an extremely rigid construction.
- Safe operation ensured by means of safety devices.
- Fully enclosed and protected pendulum.

►► APPLICATION:-

ATL Universal Testing Machine is designed for testing metals and other materials under tension, compression bending, transverse and shear loads. Hardness test on metals can also be conducted.

►► Principle of Operation

Operation of the machine is by hydraulic transmission of load from the test specimen to a separately housed load indicator. The system is ideal since it replaces transmission of load through levers and knife edges, which are prone to wear and damage due to shock on rupture of test pieces. Load is applied by a hydrostatically lubricated ram. Main cylinder pressure is transmitted to the cylinder of the pendulum dynamometer system housed in the control panel. The cylinder of the dynamometer is also of self-lubricating design. The load transmitted to the cylinder of the dynamometer is transferred through a lever system to the pendulum. Displacement of the pendulum actuates the rack and pinion mechanism which operates the load indicator pointer and the autographic recorder. The deflection of the pendulum represents the absolute load applied on the test specimen. Return movement of the pendulum is effectively damped to absorb energy in the event of sudden breakage of the specimen.

►► Machine consists of Straining Unit

This consists of a hydraulic cylinder motor with chain sprocket drive and a table coupled with the ram of the hydraulic cylinder, mounted on to a robust base. The cylinder and the ram are individually lapped to eliminate friction. The upper cross-head is rigidly fixed to the table by two straight columns.

The lower cross-head is connected to two screwed columns which are driven by a motor. Axial loading of the ram is ensured by relieving the cylinder and ram of any possible side loading by the provision of ball setting.

An displacement elongation scale with a minimum graduation of 1 mm, is provided to measure the deformation of the specimen.

Tension test is conducted by gripping the test specimen between the upper and lower cross heads. Compression, transverse, bending, shear and hardness tests are conducted between the lower cross-head and the table. The lower cross-head can be raised or lowered rapidly by operating the screwed columns, thus facilitating ease of fixing of the test specimen.

►► Control Panel

The control panel consists of a power pack complete with drive motor and an oil tank, control valves, a pendulum dynamometer, a load indicator system and an autographic recorder.

►► Power Pack

The power pack generates the 2 maximum pressure of 200 kgf/cm². The hydraulic pump provides continuously non-pulsating oil flow, Hence the load application is very smooth.

►► Hydraulic Controls

Hand operated wheels are used to control the flow to and from the hydraulic cylinder. The regulation of oil flow is infinitely variable. Incorporated in hydraulic system is a regulating valve, which maintains a practically constant rate of piston movement, Control by this valve allows extensometer readings to be taken.



TENSION TEST



ATTACHMENT FOR TENSION
TEST FOR SHOULDERED AND
THREADED SPECIMENTS



ATTACHMENT FOR TENSION
TEST FOR WIRE ROPES

►► Testing - With Economy, Speed & Versatility

►► Load Indicator System :

This system consists of a large dial and a pointer. A dummy pointer is provided to register the maximum load reached during the test. Different measuring ranges can be selected by operating the range selection knob. An overload trip switch is incorporated which automatically cuts out the pump motor when the load range in use is exceeded.

►► **Pendulum Dynamometer:**

This unit permits selection of favourable hydraulic ratios producing relatively small frictional forces. Pressurised oil in the loading cylinder pushes up the measuring piston proportionately and actuates the special dynamometer system. The piston is constantly rotated to eliminate friction. The dynamometer system is also provided with an integral damper and ensures high reliability of operation. The load transmitted to the dynamometer is transferred through a pendulum to the load indicator.

►► **Autographic Continuous Roll Load - elongation Recorder :**

This unit is of the pen and drum type and is supplied as standard. The horizontal motion of the pen produces the load ordinate of the diagram and the drum rotation produces the extension ordinates. in the ratio of either 1:5 or 1:10.

A continuous roll of graph paper is stored inside the drum and is easily replaced.


►► **Accuracy and Calibration :**

All ATL Universal Testing Machines are closely controlled for sensitivity, accuracy and calibration during every stage of manufacture. Every Machine is then calibrated over each of its measuring ranges in accordance with the procedure laid down in British Standard 1610:1992 and IS:1828-2005 Part-1.

ATL Universal Testing Machines comply with grade 'A' of BS:1610:1992 and class 1 of IS-1828 . 2005 Part-1 An accuracy of $\pm 1\%$ is guaranteed from 20% of the load range to full load. Below 20% of the selected range, the maximum permissible error is 0.2% of the full reading.



CALIBRATION OF MACHINE
WITH PROVING RING



SHEAR TEST



COMPRESSION TEST



TRANSVERSE TEST

►► **ELECTRONIC UNIVERSAL TESTING MACHINE MODEL AI-UTE**

ATL offers Electronic Models of Universal Testing Machine of all capacities as mentioned in the mechanical type. All specifications of the machine remain same. For detailed specifications of electronic system, please refer separate catalogue.



►► FEATURES :

- Micro Processor based electronic panel.
- Precision strain gauge type pressure transducer for load measurement.
- Rotary Encoder with rack for crosshead displacement indication with 0.1 mm resolution,
- Digital Load, Displacement / Extension indication
- RS-232 Com. port for PC interface.
- Data entry for specimen dimensions, serial number, gauge length, Unit selection for load etc.
- Results include Load v/s Displacement Curve, Maximum Load. Maximum Displacement, U.T.S.-% Elongation, Young's Modulus & Proof stress is Extensometer is used.

►► OPTIONAL ACCESSORIES

- X-Y plotter interface.
- Electronic load pacer.
- Crosshead displacement resolution of 0.01 mm.
- Basic Evaluation software.
- Exhaustive Evaluation software for proof stress calculation.
- Any special software on request.

►► SPECIFICATIONS

MODEL		UTM-3110	UTM-3120	UTM-3140	UTM-3160	UTM-3100	UTM-3200	UTM-3300
Maximum capacity	kN	100	200	400	600	1000	2000	3000
First Measuring Range	kN	0-100	0-200	0-400	0-600	0-1000	0-2000	0-3000
Minimum Graduation	kN	0.2	0.4	1	1	2	4	5
Second Measuring Range	kN	0-50	0-100	0-200	0-300	0-500	0-1000	0-1500
Minimum Graduations	kN	0.1	0.2	0.5	0.5	1	2	2.5
Third Measuring Range	kN	0-25	0-50	0-100	0-120	0-250	0-500	0-600
Minimum Graduation	kN	0.05	0.1	0.25	0.2	0.5	1	1
Fourth Measuring Range	kN	0-10	0-20	0-40	0-60	0-100	0-200	0-300
Minimum Graduation	kN	0.02	0.04	0.1	0.1	0.2	0.4	0.5
Clearance for tensile at fully descended working piston	mm	50-700	50-700	50-700	50-800	50-850	50-900	50-900
Clearance for compression at fully descended working piston	mm	0-700	0-700	0-700	0-800	0-850	0-900	0-900
Clearance between columns	mm	500	500	500	600	750	850	850
Ram stroke	mm	150	200	200	250	250	300	300
Straining /piston speeds (at no load)	mm / min	0-300	0-150	0-150	0-100	0-80	0-45	0-50
CONNECTED LOAD								
HP		1.3	1.3	2.3	2.5	3.5	6.5	8.5
V		400-440	400-440	400-440	400-440	400-440	400-440	400-440
Ø		3	3	3	3	3	3	3

DIMENSION								
L x W x H (approx)	mm	2032 x 750 x 1960	2032 x 750 x 1960	2060 x 750 x 2180	2265 x 750 x 2534	2415 x 815 x 2900	3000 x 1200 x 3600	3500 x 1900 x 4550
WEIGHT (approx)	kg	1500	1500	2500	3500	5500	12,500	22,000
STANDARD ACCESSORIES								
FOR TENSION TEST								
Clamping jaws for round specimens diameter	mm	10-20	10-20	10-25	10-25	10-25	20-40	25-50
	mm	20-30	20-30	25-40	25-40	25-45	40-60	50-70
	mm				40-55	45-70	60-80	70-90
Clamping jaws for flat specimens thickness	mm	0-10	0-10	0-15	0-15	0-22	0-20	0-25
		10-20	10-20	15-30	15-30	22-44	20-45	25-50
						44-65	45-70	50-75
Width	mm	50	50	65	70	70	90	100
FOR COMPRESSION TEST								
Pair of compression plates of diameter	mm	120	120	120	120	160	220	220
FOR TRANSVERSE TEST								
Table with adjustable rollers width of rollers	mm	160	160	160	160	160	200	200
Diameter of rollers	mm	30	30	30	50	50	70	70
Max.clearance between support	mm	500	500	500	600	800	900	1000
Radius of punch tops	mm	6,12	6,12	12,16	16,22	16,22	30,40	50,75

HPLC Servicing, Validation, Trainings and Preventive Maintenance :

HPLC Servicing :HPLC Servicing : We have team of service engineers who can attend to any make of HPLC promptly @the most affordable cost.

Trainings :We also take up preventive Maintenance to reduce downtime of HPLC's Trainings.

AMC's/CMC :AMC's/CMC :We offer user training both in-House and at customer sites on HPLC principles, operations, trouble-shooting.

Validations :Validations :We have protocols for carrying out periodic Validations as per GLP/GMP/USFDA norms.

Instruments :Instruments :We offer instruments/Renting Services Modules like pumps,detector etc. on Rent.



About Analytical Technologies

Analytical Technologies is synonymous for offering technologies for doing analysis and is the Fastest Growing Global Brand having presence in at least 96 countries across the global. Analytical Technologies Limited is an ISO:9001 Certified Company engaged in Designing, Manufacturing, Marketing & providing Services for the Analytical, Chromatography, Spectroscopy, Bio Technology, Bio Medical, Clinical Diagnostics, Material Science & General Laboratory Instrumentation. Analytical Technologies, India has across the Country operations with at least 4 Regional Offices, 6 Branch Offices & Service Centers. Distributors & Channel partners worldwide.

Our Products & Technologies



UV/VIS
Spectro 2080+
Double Beam



Infra FTIR



Optima Gas
Chromatograph
3007



Optima Gas
Chromatograph
2979 Plus



Flash
Chromatograph



Atomic Absorption
Spectrophotometer



Liquid Particle
Counter



Optical Emission
Spectrophotometer



DSC/TGA



Semi Auto Bio
Chemistry Analyzer



HEMA 2062
Hematology
Analyzer



Micro Plate
Reader/Washer



URINOVA 2800
Urine Analyzer



Total Organic
Carbon 3800



Fully Automated
CLIA



NOVA-2100
Chemistry Analyzer



PCR/Gradient PCR/
RTPCR



TOC
Analyzer



Laser Particle
Size Analyzer



Ion Chromatograph



Water purification
system

Regulatory compliances



Corporate Social Responsibility

Analytical Foundation is a nonprofit organization (NGO) found for the purpose of:



Analytical
Foundation

1. Research & Innovation Scientist's awards/QC Professional Award : Quality life is possible by innovation only and the innovation is possible by research only, hence ANALYTICAL FOUNDATION is committed to identify such personalities for their contributions across various field of Science and Technology and awarding them yearly. To participate for award, send us your details of research / testing / publication at Info@analyticalfoundation.org

2. Improving quality of life by offering YOGA Training courses, Work shops/Seminars etc.

3. ANALYTICAL FOUNDATION aims to DETOXYFY human minds,souls and body by means of yoga, Meditation, Ayurveda, Health Care, Awards, Media, Events, Camps etc.

Reach us @



 **Analytical**®
Technologies Limited

HPLC Solutions MultipleLabs Analytical Bio-Med Analytical Distributors Analytical Foundation (Trust)

Corporate & Regd. Office:
Analytical House, # E67 & E68,
Ravi Park, Vasna Road, Baroda,
Gujarat 390 015. INDIA

T: +91 265 2253620
+91 265 2252839
+91 265 2252370
F: +91 265 2254395

E: info@hplctechnologies.com
info@multiplelabs.com
info@analyticalgroup.net
info@analyticalbiomed.com

W. www.analyticalgroup.net
www.hplctechnologies.com
www.multiplelabs.com
www.ais-india.com

Sales & Support Offices:
across the country :
Distributors & Channel
partners World Wide