



BOD-3002

BOD Analyzer



EPCC / PRODUCTS / APPLICATION / SOFTWARE / ACCESSORIES / CONSUMABLES / SERVICES

Analytical Technologies Limited

An ISO 9001 Certified Company

www.analyticalgroup.net



Features

- Fully automatic determination of BOD content in surface water, municipal sewage and industrial waste water.
- Measurement of BOD in the water with simple and safe mercury-free pressure difference measurement method to prevent mercury poisoning caused by the leakage of mercury column;
- Choose a 7-inch high-end full-color LCD touch screen with strong reliability, a clear display control interface, full graphics and human-computer interactive operation to provide customers with the most friendly and convert operation experience;
- The data can be stored in real time and the data curve can be drawn automatically, without the conversion of the BOD concetration value directly.
- The test data can be kept without power, and the data of the unexpected power failure data will be saved automatically, and the experimental process will be carried out automatically after the power supply.
- Intelligent automatic temperature compensation, when the sample temperature is higher or lower, the meter can be automatically delayed untill the sample temperature is suitable for remeasurements.
- Support 1-6 water samples at the same time, and can detect up to 6 samples at one time.
- The training time and measurement range can be flexibly set according to actual test requirments, and the maximum support of 4000mg/L water sample is directly tested;
- The instrument is equipped with the high-end brand mini-thermal line printer, which can quickly print measurement parameters, process data and result data.
- Extra-large storage can store not less than 10000 sets of test data details, which can be checked by the data of ex-periment;
- Support for the on-line processing of test data, and all stored experimental data can be uploades to the computer by data line.



Technical Parameters:

Model	BOD-3002
Determination Range	0-4000mg/L (Subsection Measurement)
Measurement Error	Less or Less Than 10%
Sample Quantity	1-6
Storage Space	Test Data of 10000 Groups
Data Record Interval	Test Data of 10000 Groups
Measurement Period	1-30 Days Adjustable
Display Mode	7-Inch full-color LCD touch screen
Operation Mode	Touch screen full graphic human-computer interaction operation
Print Mode	Heat sensitive line type printing
Communication Interface	Standard RS232
Power Supply	220V, 50/60Hz
Packing Size(W*D*H)	500*500*400 mm
Gross Weight	15 kg

Regulatory compliances














Corporate Social Responsibility





- 1.Research & Innovation Scientist's awards/QC Professional Award : Quality life is possible by innovation only and the innovation is possible by research only, hence ANALYTICAL FOUNDATION is committed to identify such personallities for their contributions across various field of Science and Technology and awarding them yearly. To participate for award, send us your details of research / testing / publication at Info@analyticalfoundation.org
- 2. Improving quality of life by offering YOGA Training courses, Work shops/Seminars etc.
- 3. ANALYTICAL FOUNDATION aims to DETOXIFY human minds, souls and body by means of yoga, Meditation, Ayurveda, Health Care, Awards, Media, Events, Camps etc.

Reach us @





HPLC Solutions

MultipleLabs

Analytical Distributors

Analytical Foundation (Trust)

Analytical Bio-Med