



BSCC - 3212 Bacteria and Somatic Cell Count



EPCC / PRODUCTS / APPLICATION / SOFTWARE / ACCESSORIES / CONSUMABLES / SERVICES

Analytical Technologies Limited

An ISO 9001 Certified Company

www.analyticalgroup.net



Product Introduction

BSCC 3212 provides rapid hygiene testing of milk BSCC 3212 is the first-ever integrated bacteria and somatic cell tester and offers full automation for minimal reagent handling and consistent test results

Integrated bacteria and somatic cell tester

Automatic and fast a ternative to manua assay, providing instant, simultaneous results for individual bacteria and somatic cell count within 9.5 minutes and 1.5 minutes for somatic cell count alone

More accurate than alternative methods

A fully automated procedure avoids the risk of human error and inconsistency, while ready-to-use reagents in an enclosed bag system, ensure the exact same dosage for every measurement A sensor in the reagent bag indicates the number of available tests remaining. The unique reagent concept includes control samp es for quality assurance and GLP Online remote monitoring ensures consistent performance and high uptime

Simple and Flexible to use

Built on a long heritage of analytical technology and backed by global support, BSCC 3212 combines robust performance with a modern interface. Very easy-to-use with intuitive touch-screen operation for smarter money-saving decisions on how to use milk

Sample types

Raw cow's milk and buffalo milk

Parameters

Individual Bacteria Count (IBC) Somatic Cell Count (SCC)

Technology

Flow cytometry technology, counting individual bacteria cells and somatic cells The IBC results can be converted to CFU results. BSCC 3212 software includes an easy and rapid tool to develop a robust conversion table between IBC and CFU

02



>> Approvals

EURUMicrova FDA/NCIMS In compliance with ISO/IDF standards

>> Specifications

Analysis time 9.5 minutes for IBC, 1.5 minutes for SCC Analysis capacity SCC and IBC: 15 sample/hour IBC only: 15 sample/hour Sample intake IBC & SCC: 7.2 ml IBC: 6.4 ml SCC: 2.5 ml Sample temperature 2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved) Sample Quality Raw milk of normal composition and good quality. Unpreserved or preserved with azidiol Carry-over effect <1 % relative, usually <0.5% (uncompensated) IBC and SCC Working Factor IBC: 100 and SCC: 100 Measuring Range IBC: 100,000 – 1.5 mill. Cells/ml Performance Range IBC: 10,000 – 1.5 mill. Cells/ml Accuracy IBC: 100,000 – 1.5 mill. Cells/ml Accuracy IBC: 100 and SCC: VON Units from SPC (standard plate count) SCC: <10 % relative mean difference form Direct Microscopic SCC Reference or anchor Standards Plate Count (SPC) EN – ISO 4833 – 1 : 2013 method 400 x 400 x 400 mm Dimension (W x H x D) Approx. 600 x 630 mm Power Consumption Max 190 VA Water supply for Purified water(<5 µS/cm3) preparation The instruments does not require a direct connection to water	Feature	Specification
IBC only: 15sample/hourSCC only: 40 sample/hourSCC only: 40 sample/hourSCC only: 40 sample/hourSample intakeIBC & SCC: 7.2 ml IBC: 6.4 ml SCC: 2.5 mlSample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC	Analysis time	9.5 minutes for IBC, 1.5 minutes for SCC
sample/hourSCC only: 40 sample/hourSample intakeIBC & SCC: 7.2 ml IBC: 6.4 ml SCC: 2.5 mlSample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC	Analysis capacity	
40 sample/hourSample intakeIBC & SCC: 7.2 ml IBC: 6.4 ml SCC: 2.5 mlSample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1% relative, usually <0.5% (uncompensated) IBC and SCC		
Sample intakeIBC & SCC: 7.2 ml IBC: 6.4 ml SCC: 2.5 mlSample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC		
IBC: 6.4 ml SCC: 2.5 mlSample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC		
SCC: 2.5 mlSample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC	Sample intake	
Sample temperature2 - 42 °C (35.6-107.6 F) (preserved) 2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC		
2 - 4 degrees °C (non-preserved)Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC		
Sample QualityRaw milk of normal composition and good quality. Unpreserved or preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC	Sample temperature	
preserved with azidiolCarry-over effect<1 % relative, usually <0.5% (uncompensated) IBC and SCC		
Working FactorIBC: 100 and SCC: 100Measuring RangeIBC: 5000-20 mill IBC/ml (approx. 1,500 to 10 mil CFU/ml) SCC: 0-10 mil. Cells/mlPerformance RangeIBC: 10,000 – 10 mill. IBC/ml SCC: 1000,000 – 1.5 mill. Cells/mlAccuracyIBC: Typical Sy, x < 0.25 log units from SPC (standard plate count) SCC: < 10 % relative mean difference form Direct Microscopic SCC	Sample Quality	
Measuring RangeIBC: 5000-20 mill IBC/ml (approx. 1,500 to 10 mil CFU/ml) SCC: 0-10 mil. Cells/mlPerformance RangeIBC: 10,000 – 10 mill. IBC/ml SCC: 1000,000 – 1.5 mill. Cells/mlAccuracyIBC: Typical Sy, x < 0.25 log units from SPC (standard plate count) SCC: < 10 % relative mean difference form Direct Microscopic SCC	Carry-over effect	<1 % relative, usually <0.5% (uncompensated) IBC and SCC
SCC: 0-10 mil. Cells/mlPerformance RangeIBC: 10,000 – 10 mill. IBC/ml SCC: 1000,000 – 1.5 mill. Cells/mlAccuracyIBC: Typical Sy, x < 0.25 log units from SPC (standard plate count) SCC: < 10 % relative mean difference form Direct Microscopic SCC	Working Factor	IBC: 100 and SCC: 100
Performance RangeIBC: 10,000 – 10 mill. IBC/ml SCC: 1000,000 – 1.5 mill. Cells/mlAccuracyIBC: Typical Sy, x < 0.25 log units from SPC (standard plate count) SCC: < 10 % relative mean difference form Direct Microscopic SCC	Measuring Range	IBC: 5000-20 mill IBC/ml (approx. 1,500 to 10 mil CFU/ml)
SCC: 1000,000 – 1.5 mill. Cells/mlAccuracyIBC: Typical Sy, x < 0.25 log units from SPC (standard plate count) SCC: < 10 % relative mean difference form Direct Microscopic SCC		SCC: 0-10 mil. Cells/ml
AccuracyIBC: Typical Sy, x < 0.25 log units from SPC (standard plate count) SCC: < 10 % relative mean difference form Direct Microscopic SCCReference or anchor methodStandards Plate Count (SPC) EN – ISO 4833 – 1 : 2013Dimension (W x H x D)400 x 400 x 400 mmWeight25 kgSpace requirements (W x D)Approx. 600 x 630 mmPower Supply110 – 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Performance Range	IBC: 10,000 – 10 mill. IBC/ml
SCC: < 10 % relative mean difference form Direct Microscopic SCCReference or anchor methodStandards Plate Count (SPC) EN – ISO 4833 – 1 : 2013Dimension (W x H x D)400 x 400 x 400 mmWeight25 kgSpace requirements (W x D)Approx. 600 x 630 mmPower Supply110 – 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 µS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	_	SCC: 1000,000 – 1.5 mill. Cells/ml
Reference or anchor methodStandards Plate Count (SPC) EN – ISO 4833 – 1 : 2013Dimension (W x H x D)400 x 400 x 400 mmWeight25 kgSpace requirements (W x D)Approx. 600 x 630 mmPower Supply110 – 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 µS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Accuracy	IBC: Typical Sy, x < 0.25 log units from SPC (standard plate count)
methodImage: Constraint of Const		SCC: < 10 % relative mean difference form Direct Microscopic SCC
Dimension (W x H x D)400 x 400 x 400 mmWeight25 kgSpace requirements (W x D)Approx. 600 x 630 mmPower Supply110 - 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 - 35 °C (41 - 95 °F)Relative humidity<93 % RH	Reference or anchor	Standards Plate Count (SPC) EN – ISO 4833 – 1 : 2013
Weight25 kgSpace requirements (W x D)Approx. 600 x 630 mmPower Supply110 – 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	method	
Space requirements (W x D)Approx. 600 x 630 mmPower Supply110 – 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Dimension (W x H x D)	400 x 400 x 400 mm
Power Supply110 – 240 V AC, 50/60 HzPower ConsumptionMax 190 VAWater supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Weight	25 kg
Power ConsumptionMax 190 VAWater supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Space requirements (W x D)	Approx. 600 x 630 mm
Water supply for preparationPurified water(<5 μS/cm3) The instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Power Supply	110 – 240 V AC, 50/60 Hz
preparationThe instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH		
preparationThe instruments does not require a direct connection to water tap but forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	Water supply for	Purified water(<5 μS/cm3)
forchemical preparation ultra pure (de-mineralized water must be available)WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH	preparation	
WasteMax 1 Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH		
Ambient temperatureAmbient temperature 5 – 35 °C (41 – 95 °F)Relative humidity<93 % RH		
Relative humidity <93 % RH	Waste	
Relative humidity <93 % RH	Ambient temperature	Ambient temperature 5 – 35 $^{\circ}$ C (41 – 95 $^{\circ}$ F)

03



Repeatability				
Range (IBC/µl)	S _r (log – units)	Typical S _r (log – units)		
10 - 50	0.07	0.06		
51 – 200	0.05	0.04		
>200	0.04	0.02		
Entire Range	0.05			
Reproducibility (between instruments)				
Range (IBC/ µl)	S _R (log – units)	Typical S _R (log – units)		
10-50	0.11	0.08		
51 – 200	0.07	0.06		
>200	0.06	0.04		

Repeatability		
Range (SCC/µl)	CV, %	
100 - 299	6	
300 – 499	4	
>500	3	
Reproducibility		
Range (SCC/µl)	S _{R,} %	
100 - 299	7	
300 - 499	5	
>500	4	







HPLC Servicing, Validation, Trainings and Preventive Maintenance :

HPLC Servicing :HPLC Servicing : We have team of service engineers who can attend to any make of HPLC promptly @the most affordable cost. Trainings :We also take up preventive Maintenace to reduce downtime of HPLC's Trainings. AMC's/CMC :AMC's/CMC :We offer user training both in-House and at customer sites on HPLC principles, operations, trouble-

Validations :Validations :We have protocols for carrying out periodic Validations as per GLP/GMP/USFDA norms.

Instruments :Instruments :We offer instruments/Renting Services Modules like pumps.detector etc. on Rent.



About Analytical Technologies

shooting.

Analytical Technologies is synonymous for offering technologies for doing analysis and is the Fastest Growing Global Brand having presence in at least 96 countries across the global. Analytical Technologies Limited is an ISO:9001 Certified Company engaged in Designing, Manufaturing, Marketing & providing Services for the Analytical, Chromatography, Spectroscopy, Bio Technology, Bio Medical, Clinical Diagnostics, Material Science & General Laboratory Instrumentation. Analytical Technologies, India has across the Country operations with at least 4 Regional Offices, 6 Branch Offices & Service Centers. Distributors & Channel partners worldwide.

Optima Gas

Chromatograph

2979 Plus

Our Products & Technologies







Optical Emission Spectrophotometer



Infra FTIR



DSC/TGA



Chromatograph 3007



Semi Auto Bio





HEMA 2062

Hematology



Flash Chromatograph



Micro Plate Reader/Washer









Liquid Partical Counter



Total Organic Carbon 3800



Fully Automated CLIA

NOVA-2100 Chemistry Analyzer

PCR/Gradient PCR/ RTPCR

TOC Analyzer

Laser Particle Size Analyzer

Ion Chromatograph

Water purification system



Spectrophotometer

URINOVA 2800

Urine Analyzer

Regulatory compliances



Corporate Social Responsibility

Analytical

Foundation

Analytical Foundation is a nonprofit organization (NGO) found for the purpose of:

1.Research & Innovation Scientist's awards/QC Professional Award : Quality life is TΜ possible by innovation only and the innovation is possible by research only, hence ANALYTICAL FOUNDATION is committed to identify such personallities for their contributions across various field of Science and Technology and awarding them yearly. To participate for award, send us your details of research / testing / publication at Info@analyticalfoundation.org

> 2. Improving quality of life by offering YOGA Training courses, Work shops/Seminars etc.

> 3. ANALYTICAL FOUNDATION aims to DETOXIFY human minds, souls and body by means of yoga, Meditation, Ayurveda, Health Care, Awards, Media, Events, Camps etc.



R Analytical **Technologies Limited**

HPLC Solutions MultipleLabs

Analytical Bio-Med

Analytical Distributors Analytical Foundation (Trust)

Corporate & Regd. Office: Analytical House, # E67 & E68, Ravi Park, Vasna Road, Baroda, Gujarat 390 015. INDIA

+91 265 2252839 +91 265 2252370 F: +91 265 2254395

T: +91 265 2253620

E: info@hplctechnologies.com info@multiplelabs.com info@analyticalgroup.net

W. www.analycalgroup.net www.hplctechnologies.com www.multiplelabs.com

Sales & Support Offices: across the country : **Distributors & Channel** partners World Wide