





INFRA3000 FTIR

Products | Applications | Software | Accessories | Consumables | Services

Analytical Technologies Limited www.analyticalgroup.net

(01)



Features :

- New type cube corner Michelson interferometer features smaller size and structure, providing higher stability and less sensitive to vibrations and thermal variations than conventional Michelson interferometer.with 5 year warranty
- Fully sealed damp and dust proof interferometer, adopting Fully sealed damp and dustproof interferometer, adopting ensures higher adaptability to the environment and increases accuracy and reliability in operation. Viewable window for silicagel enables easy observation and replacement.
- Isolated MID IR source and large space heat dissipation chamber design provides higherthermal stability and Self-Compensation Stable interference is obtained without the need of dynamic adjustment.
- SNR is calculated value that represents the ratio of RMS signal to RMS noise.
- The peak value is the highest voltage that the waveform will ever reach
- All optics and mirrors are aluminum coated
- Reliable calibration mechanism
- Critical components checked prior to every scan
- Automatic recognition of accessories
- Temperature controlled and moisture resistant optics
- High intensity MID IR source adopts a reflex sphere to obtain even and stable IR
- radiation. Cooling fan stretch suspending design ensures good mechanical stability and multimediatutorials.
- Super wide sample compartment provides more flexibility to accommodate various accessories.
- Built in purge facility with sealed and desiccated optical set up with 5 years desiccant replacement.
- The application of programmable gain amplier, high accuracy A/D converter and embedded computer improves the accuracy and reliability of the whole system
- The spectrometer connects to PC via a USB port or Ethernet cable for automatic control and data communication, fully realizing plug-and-play operation
- Compatible PC control with user friendly, rich function software enables easy, convenientand operation.Spectrum collection, spectrum conversion, spectrum processing,
- spectrumanalyzing, and spectrum output function etc. can be performed.
 Various special IR libraries are available for routine search.Users can also add and
- maintain the libraries or set up new libraries by themselves.
- Vibration isolated base plate Accessories such as Defused/Specular reflection, ATR, Liquid Cell, Gas Cell, and
- IRmicroscope etc. can be mounted in the sample compartment.
- Minimizes the effect of atmospheric water and CO₂ interference.
- Facilitated with high longevity and stable interferometer
- Auto and manual subtraction of CO₂ and H₂O absorption are available.
- Determination of both solid and liquid samples.
 Sample Analysis: solid, liquid, paste, powder, gel and mixture samples without sample preparation

>> Specifications :

- 🔆 Analytical **Technologies** Limited
- Spectral Range : 7800 to 375cm⁻¹ Resolution : Better than 0.85cm⁻¹ (Model 3000A) Better than 0.5cm⁻¹ (Model 3000B) Wavenumber Precision : ± 0.01 cm⁻¹ at 2000 cm⁻¹ Wavenumber Accuracy : ± 0.01 cm⁻¹ at 2000 cm⁻¹ Wave number reproducibility : 0.05 cm⁻¹ Scanning Speed : 5 - step adjustable for applications (16 scan/min) Signal to noise ratio(SNR) : better than 55,000:1 (RMS value, at 2100cm⁻¹, resolution : 4cm⁻¹,1minute data collection) Detector : DTGS/DLaTGS detector cover full range equipped with temperature control mechanism, Software Controlled detector selection Optics : Kinematically mounted, Zero alignment optics, with high reflectivity and low angle off axis design Desiccant : Long life desiccant system with software controlled desiccant status indicator with 20x10gm of **Rechargeable Desiccant** Beam Splitter : Ge coated Kbr (Optional: ZnSe beam splitter) (The beam splitters shall be moisture resistant and capable of with standing high humidity) Infrared Source : Air-cooled, high efficiency Reflex Sphere module (long life mid IR source) with 5 year warranty Data System : Compatible computer Software : FTIR software contains all routines needed for basic spectro meter operations, including library search, quantitation and spectrum export. A single software platform Containing interpretation, report builder, IR analysis, comparison, auto atmospheric correction, online data acquisition, baseline correction, smoothening and plot overlay.21 CFR Part 11 complied software IR Library : Built in library with minimum 2500 Reference spectra for drugs. : 54 x 52 x 26 cm Dimensions • Weight : 28 Ka Operation of Instrument : 220-240 V/ 50/60 Hz : 5-45°C Operating temperature range : 10-90% Humidity Range Window
- Pellet press

- : Humid resistant Window
- : capable of making pellets with controlled pressure
 - (03)



Accessories:

Diffuse / Specular Reflectance Accessory

It is a versatile diffuse reflectance and specular reflectance accessory. Diffuse reflection mode is used for transparent and powder sample analysis. Specular reflection mode is for measuring smooth reflective surface and coating surface.

- High light throughput
- · Easy operation, no internal adjustment needed
- Optical aberration compensation
- Small light spot, able to measure micro samples
- Variable angle of incidence
- Fast change of powder cup

Horizontal ATR / Variable Angle ATR (30° ~ 60°)

Horizontal ATR is suitable for the analysis of rubber, viscous liquid, large surface and pliable solids etc. Variable angle ATR is used for measurement of films, painting (coating) layers and gels etc.

- Easy installation and operation
- High light throughput
- Variable depth of IR penetration

IR Microscope

- Micro samples analysis, minimum sample size: 100mm (DTGS detector) and 20mm (MCT detector)
- Translucent sample analysis
- Two measurement methods: transmission and reflection
- Easy sample preparation

Single Reflection ATR

It provides high throughput when measuring materials with high absorption, such as polymer, rubber, lacquer, fiber etc.

- High throughput
- Easy operation and high analytical efficiency
- ZnSe, Diamond, AMTIR, Ge and Si Crystal plate can be selected according to application.













Accessory for Determination of Hydroxyl in IR Quartz

- Fast, convenient and accurate measurement of Hydroxyl content in IR quartz
- Direct measurement to IR quartz tube, no need to cut samples
- Accuracy : £ 1 x 10⁻⁶ (£ 1ppm)

Accessory for Oxygen and Carbon in Silicon Crystal Determination

- Special silicon plate holder
- Automatic, fast and accurate measurement of oxygen and carbon in silicon crystal
- Lower detection limit : 1.0 x 10¹⁶ CM⁻³ (at room temperature)

Sio₂ Powder Dust Monitoring Accessory

- Special Sio₂ Powder Dust Monitoring software
- Fast and accurate measurement of Sio₂ Powder Dust

Component Testing Accessory

- Fast and accurate measurement of the response of such components as MCT, InSb and PbS etc.
- Curve, peak wavelength, stop wavelength and D* etc can be presented

Optic Fiber testing Accessory

• Easy and accurate measurement of the loss rate of IR optic overcoming the difficulties for testing, since they are very thin, with very small light passing holes and uneasy to fix.

05


Jewelry Inspection Accessory


• Accurate of Jewelries.


Universal Accessories

- · Fixed liquid cells and demountable liquid cells
- Gas cells with pathlength









Regulatory compliances



Corporate Social Responsibility

Analytical Foundation is a nonprofit organization (NGO) found for the purpose of:



1.Research & Innovation Scientist's awards/QC Professional Award : Quality life is possible by innovation only and the innovation is possible by research only, hence ANALYTICAL FOUNDATION is committed to identify such personallities for their contributions across various field of Science and Technology and awarding them yearly. To participate for award, send us your details of research / testing / publication at Info@analyticalfoundation.org

2. Improving quality of life by offering YOGA Training courses, Work shops/Seminars etc.

3. ANALYTICAL FOUNDATION aims to DETOXIFY human minds, souls and body by means of yoga, Meditation, Ayurveda, Health Care, Awards, Media, Events, Camps etc.





Technologies Limited

HPLC Solutions Corporate & Regd. Office: Analytical House, # E67 & E68,

Ravi Park, Vasna Road, Baroda,

Gujarat 390 015. INDIA

T +91 265 2253620 +91 265 2252839 +91 265 2252370 F: +91 265 2254395

MultipleLabs

Analytical Bio-Med **Analytical Distributors** E: info@hplctechnologies.com

info@multiplelabs.com

info@analyticalgroup.net

info@analyticalbiomed.com

Analytical Foundation (Trust)

W. www.analvcalgroup.net www.hplctechnologies.com www.multiplelabs.com www.ais-india.com

Sales & Support Offices: across the country : **Distributors & Channel** partners World Wide

Reach us @